



KAISHAN COMPRESSOR

SPPECIFICATION SHEET

Product information

Model	KRSL-200-45
Cooling	Air cooled
Power Supply - voltage	460V
Power Supply - Frequency	60Hz
Power Supply - Phases	3-Phase
Typen of drive	Direct
Maximum ambient temperature - °F	115
Minimum ambient temperature - °F	32

Compressor performance*

Rated Working Pressure - psig	36
Minimum working pressure - psig	30
Maximum working pressure - psig	45
Capacity at rated Working Pressure - acfm	2020
Total input Power at rated Working Pressure – kW	181.0
Specific Power at rated Working Pressure-kW/100 cfm	9.0

Motor Data (Typical)

Motor rated HP	200
Motor Nominal Efficiency %	96.2%
Motor frame	TEFC
Service Factor	1.3
Starter Type	Y-Δ
Motor Protection	IP54

Dimensions & Weights w/Enclosure Air-cooled Series

Length - in	157
Width - in	81
Height - in	88
Weight - lbs	13051
Discharge Pipe Size	NPS6
Moisture Drain Connection	-

dBA Ratings at 3 feet (Typical)

Air – cooled enclosure - dBA	76
------------------------------	----



KAISHAN COMPRESSOR

SPPECIFICATION SHEET

Cooling Air Flows

Cooling fan capacity - cfm	15185
Fan Motor - HP	7
Cooling fan	Centrifugal

Filter Rating

Inlet Air	99.9% Eff.
Oil Filter	23µm
Fluid Carryover(PPM)	3ppm

Product features

Airend	Single stage
Motor brand	WEG
Motor type	IEC
Control Type	Modulation
Enclosure/Cabinet type	Low sound