



## Maryville, TN

### SCOPE

---

**Model:** VF-200  
**Application:** \_\_\_\_\_  
**Options:** \_\_\_\_\_

### OPERATING CONDITIONS

---

<b>Air Flow Rate (SCFM)</b>	200
<b>Inlet Air Operating Pressure (PSIG)</b>	100
<b>Inlet Air Temperature (°F)</b>	100
<b>Relative Humidity (%)</b>	100
<b>Minimum Ambient Temperature (°F)</b>	32
<b>Maximum Ambient Temperature (°F)</b>	100
<b>Maximum Inlet Temperature (°F)</b>	100
<b>Maximum Pressure (PSIG)</b>	200
<b>Air Pressure Drop (PSI)</b>	<5
<b>Air Temperature at Dryer Outlet (°F)</b>	69-80
<b>Outlet Dew Point (°F)</b>	38

### DRYER ASSEMBLY

---

<b>Height (in.)</b>	30
<b>Width (in.)</b>	36
<b>Depth (in.)</b>	25
<b>Weight (lbs.)</b>	240
<b>Inlet/Outlet Connections (in.)</b>	1.5

### ELECTRICAL DETAILS

---

<b>Electrical Connection</b>	230-1-60
<b>Condensing Unit Power (KW)</b>	1.35
<b>Compressor LRA (Amp)</b>	55.0
<b>Compressor RLA (Amp)</b>	12.6
<b>Min Circuit (Amp)</b>	16.9
<b>Electrical Protection Class</b>	NEMA 1

## SYSTEM DETAILS

---

<b>Drain Outlet Connection (in.)</b>	0.25
<b>Number of Drains</b>	1
<b>Drain Type</b>	Timer
<b>Noise Level (dB)</b>	< 85

### Heat Exchanger:

<b>Heat Exchanger Volumetric Flow Rate (SCFM)</b>	200
<b>Number of Heat Exchangers</b>	1
<b>Air to Air Heat Exchanger Type</b>	Aluminum Plate-Fin
<b>Air to Refrigeration Heat Exchanger Type</b>	Aluminum Plate-Fin
<b>Separator Type</b>	Internal Demister

### Condensing Unit:

<b>Type of Cooling</b>	Air-Cooled
<b>Type of Refrigerant</b>	R-134a
<b>Nominal HP</b>	1 1/4
<b>Condenser Air Flow Rate (CFM)</b>	650
<b>Capacity Control</b>	Hot Gas Bypass Valve
<b>Expansion System</b>	Thermal Expansion Valve

### Refrigeration:

<b>Refrigerant Charge</b>	3 lbs. 0 oz.
<b>Refrigerant Compressor Type</b>	Scroll
<b>Maximum Suction (PSIG)</b>	65
<b>Minimum Suction (PSIG)</b>	28
<b>Maximum Discharge (PSIG)</b>	230
<b>Minimum Discharge (PSIG)</b>	100

### Fan:

<b>Fan Motor Quantity</b>	1
<b>Amps Per Motor</b>	0.85
<b>Motor Power Consumption (W)</b>	135
<b>Motor Size (HP)</b>	0.067