


#### TECHNICAL INFORMATION

MAX. INLET FLOW RATE: 300 CFM  
SWEEP AIR FLOW RATE @ 175 PSI: 24 CFM  
MAX. PRESSURE: 175 PSI  
MIN. RECOMMENDED PRESSURE: 80 PSI  
MAX. INLET AIR TEMPERATURE: 150 °F  
POWER: 120 VAC, 0.19 AMPS

02	Update ERP BOM & Inst. Instr.	05/21/24	CDG
01	New safety relief valve	03/04/24	CDG
000	Initial Release	02/23/23	CDG
NO.	REVISION	DATE	APPR


#### THIRD ANGLE PROJECTION



**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SUBURBAN MANUFACTURING INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUBURBAN MANUFACTURING INC IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±1° BEND ±2° FRACTIONAL: ± 1/16 ONE PLACE DECIMAL ± 0.050 TWO PLACE DECIMAL ± 0.010 THREE PLACE DECIMAL ± 0.005 FOUR PLACE DECIMAL ± 0.0005 INTERPRET GEOMETRIC TOLERANCING PER: ANSI Y14.5 - 2009	
MATERIAL	
FINISH	125
DO NOT SCALE DRAWING	

	INITIALS	DATE
DESIGNED	JSM	11/17/21
DRAWN	JSM	05/20/24
MFG ENG APPR.		
ENG APPR.	CDG	05/21/24
COMMENTS:		



**SUBURBAN**  
MANUFACTURING GROUP

TITLE: 300 CFM (75Hp) Tsunami Regenerative Drying System - Rail Mounted

DWG. NO. <b>21999-0755</b>	REV <b>02</b>
SIZE: B SCALE: 1:10 WEIGHT:	SHEET 1 OF 1