



An
Employee
Owned
Company

30-Gallon Air Compressor

Two Stage — Electric



AM2-P305-30K



In-line air tool lubricator



PL-1530A twist lock plug with shroud

Designed with a powder coated ASME receiver tank, you will experience proven performance from this 30-gallon air compressor time after time.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

FRAME

- Powder coated ASME receiver tank
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removable base plate offers flexible installation
- 10-inch flat-free tires

COMPONENTS

- Two regulated air outlet connections
- Two gauges for tank and outlet pressure
- In-line air tool lubricator
- Manual drain valves for proper maintenance
- 16½-inch fly wheel
- Industrial-grade pressure switch

LIMITED WARRANTY

- 1 year electric motor

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM

MODEL NUMBER	CFM @ PSI*	HORSEPOWER/MOTOR	RPM	PLUG TYPE	UNIT DIMENSIONS (LxWxH)	SHIPPING DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-P305-30K	16.9 @ 175	208-230V, 3Ø, 13-12.2A Baldor	1740	PL-1530A twist lock with shroud	49.5x27x43.5in.	57x37x47in.	491 lb.	400 lb.

*Equipped with 150-PSI maximum rated regulator.

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

