

BULLET D 80 with Generator

Rotary Screw Air Compressor & Generator

BIG ENOUGH TO HANDLE THE TOUGHEST JOBS...



PERFECT FOR A 90LB. JACK HAMMER!





COMPACT DESIGN

The $BOSS^{\otimes}$ Bullet D is a compact, strategically designed system which integrates all major components on to a single frame, enclosed in a tough, weather-resistant canopy.

The Bullet D design provides output of up to 80cfm at 100psi.

Because it measures just 24" wide x 54" long x 40" high and only weighs 775lbs, the *Bullet D* can be set on any class truck with minimal effect on load capacity and visibility. It is narrow enough to fit into standard industrial gates and doorways, as well as service elevators for high rise or underground construction. The 20" base width of the *Bullet D* makes it ideal for mounting on top of a 20" wide service body compartments.

ROTARY SCREW DEPENDABILITY

The heart of the *BOSS Bullet D* compressor is the rotary screw air-end. Rotary screw compression is ideal for this application because it provides constant air flow and pressure, regardless of the amount of time it takes to get the job done. This eliminates the need for an air storage tank, there is no waiting for the system to "catch-up".

DIESEL ENGINE PERFORMANCE

Strong, dependable, efficient, all the words you want to hear when choosing the right product for the right job. When performance matters, choosing the right air compressor and paired with the right engine makes all the difference, that's why we choose the KUBOTA Water Cooled Final Tier 4 engine.

COMPRESSOR OPTIONS

- Dual Pressure
- Remote Start/Stop

GENERATOR PERFORMANCE

Single function performance:

80cfm @100psi / up to 6.0kW


63cfm @100psi / 7.5kW

Multi-function performance:


35cfm @100psi / 7.5kW

40cfm @100psi / 6.0kW

60cfm @100psi / 3.5kW



3.07



DISTRIBUTED BY:

48.00



BOSS INDUSTRIES, LLC.

1761 Genesis Drive LaPorte, IN 46350 Voice: (219) 324-7776 • (800) 635-6587 • Fax: (219) 324-7470 Electronic: www.bossair.com • email: sales@bossair.com

Specifications subject to change without notice. ©2021 Boss Industries, LLC. Printed In U.S.A. Bullet D 80. N/A. 12/23/21. BI

ENGINE

Enterne	
Туре	KUBOTA D902-E3B Final Tier 4, Vertical 4-cycle, Water Cooled Diesel Engine
Engine Warranty	2 years/2,000 Hours
Power (@3600 rpm)-hp	24.8
Displacement-cu. in3.	54.8 Cubic Inches
Bore-in., Stroke-in.	2.83" x 2.90"
Oil pan capacity	.98 Gal.
Battery Rating Volts	12v - 580CCA @ 0°F
Fuel tank capacity	None - Designed to run off of vehicle tank

COMPRESSOR

Туре	Oil Flooded Rotary Screw
Rated Delivery	80cfm
Rating Operating Pressure	100psig*
Operating Pressure Range	80 - 115psig
Max. Operating Temp.	+100° F
Oil Sump Capacity	2.0 gallons
Air Service Connection	One 3/4" NPT

GENERAL INFORMATION	(Metrics in Parenthesis)
Weight	775lbs (Dry)
Dimensions	53.99" L x 23.59" W x 37.63" H

Bullet D with Generator