





THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE UPON PRODUCTION.

UNLESS OTHERWISE SPECIFIED: -DIMENSIONS ARE IN INCHES -REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY -FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

	A CONVERTED TO	0.30		I	-	EZR U	04/25/10	NAD
		ELEMENT SPECS						
		PART NUMBER				825		
			MATERIAL		825 Polyester			
			FLOW RATE	25 CFM		0iyester 42 m ³ /hr		
			SURFACE AREA		ft ²		42 m ² /hr	
			I.D.		50"		<u> </u>	
			0.D.		50"	_	64mm	
			HEIGHT		59"		68mm	
	MODEL #: CSL-825-039HCB	MATERIAL: CARBON STEEL			FINISH: BLACK POWDER			
	MODEL NUMBER: CSL-825-039HCB						S	HEET:
							1	OF 1
	DESCRIPTION: CSL-825-039HCB, BLA	(CK						
	PROJECT:	DRAWN	BY: SR	APPR	OVED BY	′ :		REV:
-	SD15174		12/23/2009	DATE:				A
-		<u></u>						

REVACONVERTED TO 3D

DESCRIPTION

 ECN #
 CHG BY
 DATE
 APP'D

 EZR
 04/25/16
 NAD