





THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE UPON PRODUCTION.

UNLESS OTHERWISE SPECIFIED: -DIMENSIONS ARE IN INCHES -REF: APPROXIMATE DIMENSIONS, NO TOLERANCES API -FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER



	ELEMENT SPECS						
		PART NUMBER	82	25			
			MATERIAL	Polyester			
		FLOW RATE	25 CFM	42 m³/hr			
			SURFACE AREA	0.4 ft ²	0.0 m ²		
			I.D.	1.50"	38mm		
			O.D.	2.50"	64mm		
			HEIGHT	2.69"	68	mm	
	MODEL #: CSL-825-075HCB	MATE	FINISH: BLACK POWE				
	MODEL NUMBER: CSL-825-075HCB					SHEET: 1 OF 1	
GE	DESCRIPTION: CSL-825-075HCB, BLACK						
APPLY R	PROJECT:	DRA	WN BY: RWK	APPROVED BY:			REV:
		DATI	E: 9/30/2019	DATE:			