Cube Air System 5 HP Reciprocating

18 cfm @ 175 psi

Basic Compressor Features:

- Cast iron reciprocating compressor pump
- Centrifugal unloader
- Disc and spring valves
- Discharge cooling manifold
- Easy open inline check valve
- Easy service belt guard
- Easy to read oil sight glass
- Easy service reciprocating pump platform
- Extended oil drain tube
- Industrial grade electric drive motor
- **I** Inner stage cooler
- Minimal floor space foot print
- Multiplexing capability
- Rigid steel frame construction
- Self tensioning electric motor base

Optional Package Features:

- Class 1 Div 2 drive motor
- Coalescing filtration
- Desiccant air dryer
- Electronic automatic tank drain kit (shipped loose for installation on site)
 Kit includes: drain, ¼ pipe street 90 elbow, ¼ pipe 6 inch nipple
- Enrollment in factory extended service program
- Enrollment in factory extended warranty plan
- Multiplex control panel
- NEMA 4X electrical components
- NEMA 7 electrical components
- Particulate filtration
- Quick Install Kit Includes:
 8ft electrical cord with plug, 6ft
 compressor to tank air line JIC fittings,
 6ft tank to facility air line JIC fittings
- Reciprocating Pump Enclosure for noise reduction
- Refrigerated air dryer
- 30, 60, 80, 120, gallon storage tank (200 psi MWP, ASME, CRN)

Platinum Compressor Features:

- All basic compressor features
- Belt guard mounted air after cooler
- Low oil monitor
- High-temp stainless steel flex discharge line
- Vibration isolation mounting pads
- Freight pre-paid in standard freight area




| Model | Phase | Voltage | Length | Width | Height | Weight | Amp Draw 230 Volt |
|-------|-------|-----------------|--------|-------|--------|--------|----------------------|
| IGQ51 | 1 | 208-230 | 26.25 | 22.5 | 40 | 350 | 24 |
| IGQ53 | 3 | 208-230/460-480 | 26.25 | 22.5 | 40 | 350 | 16 |

Add -P to model number to make Platinum Unit All dimensions are in inches, weight is in pounds, 480 volt amp draw were applicable is approximately $\frac{1}{2}$ or 230 volt amp draw

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.







Cube Air System 7.5 HP | 28 cfm Reciprocating

28 cfm @ 175 psi

Basic Compressor Features:

- Cast iron reciprocating compressor pump
- Centrifugal unloader
- Disc and spring valves
- Discharge cooling manifold
- Easy open inline check valve
- Easy service belt guard
- Easy to read oil sight glass
- Easy service reciprocating pump platform
- Extended oil drain tube
- Industrial grade electric drive motor
- **I** Inner stage cooler
- Minimal floor space foot print
- Multiplexing capability
- Rigid steel frame construction
- Self tensioning electric motor base

Optional Package Features:

- Class 1 Div 2 drive motor
- Coalescing filtration
- Desiccant air dryer
- Electronic automatic tank drain kit (shipped loose for installation on site)
 Kit includes: drain, ¼ pipe street 90 elbow, ¼ pipe 6 inch nipple
- Enrollment in factory extended service program
- Enrollment in factory extended warranty plan
- Multiplex control panel
- NEMA 4X electrical components
- NEMA 7 electrical components
- Particulate filtration
- Quick Install Kit Includes:
 8ft electrical cord with plug, 6ft
 compressor to tank air line JIC fittings,
 6ft tank to facility air line JIC fittings
- Reciprocating Pump Enclosure for noise reduction
- Refrigerated air dryer
- 30, 60, 80, 120, gallon storage tank (200 psi MWP, ASME, CRN)

Platinum Compressor Features:

- All basic compressor features
- Belt guard mounted air after cooler
- Low oil monitor
- High-temp stainless steel flex discharge line
- Vibration isolation mounting pads
- Freight pre-paid in standard freight area




| Model | Phase | Voltage | Length | Width | Height | Weight | Amp Draw 230 Volt |
|---------|-------|-----------------|--------|-------|--------|--------|----------------------|
| IGQ71-6 | 1 | 208-230 | 30 | 22.5 | 40 | 450 | 32 |
| IGQ73-6 | 3 | 208-230/460-480 | 30 | 22.5 | 40 | 450 | 18 |

Add -P to model number to make Platinum Unit All dimensions are in inches, weight is in pounds, 480 volt amp draw were applicable is approximately $\frac{1}{2}$ or 230 volt amp draw

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.







Cube Air System 10 HP Reciprocating

35 cfm @ 175 psi

Basic Compressor Features:

- Cast iron reciprocating compressor pump
- Centrifugal unloader
- Disc and spring valves
- Discharge cooling manifold
- Easy open inline check valve
- Easy service belt guard
- Easy to read oil sight glass
- Easy service reciprocating pump platform
- Extended oil drain tube
- Industrial grade electric drive motor
- **I** Inner stage cooler
- Minimal floor space foot print
- Multiplexing capability
- Rigid steel frame construction
- Self tensioning electric motor base

Optional Package Features:

- Class 1 Div 2 drive motor
- Coalescing filtration
- Desiccant air dryer
- Electronic automatic tank drain kit (shipped loose for installation on site) Kit includes: drain, ¼ pipe street 90 elbow, ¼ pipe 6 inch nipple
- Enrollment in factory extended service program
- Enrollment in factory extended warranty plan
- Multiplex control panel
- NEMA 4X electrical components
- NEMA 7 electrical components
- Particulate filtration
- Quick Install Kit Includes:
 8ft electrical cord with plug, 6ft
 compressor to tank air line JIC fittings,
 6ft tank to facility air line JIC fittings
- Reciprocating Pump Enclosure for noise reduction
- Refrigerated air dryer
- 30, 60, 80, 120, gallon storage tank (200 psi MWP, ASME, CRN)

Platinum Compressor Features:

- All basic compressor features
- Belt guard mounted air after cooler
- Low oil monitor
- High-temp stainless steel flex discharge line
- Vibration isolation mounting pads
- Freight pre-paid in standard freight area



| Model | Phase | Voltage | Length | Width | Height | Weight | Amp Draw 230 Volt |
|--------|-------|-----------------|--------|-------|--------|--------|----------------------|
| IGQ101 | 1 | 208-230 | 30 | 22.5 | 40 | 450 | 42 |
| IGQ103 | 3 | 208-230/460-480 | 30 | 22.5 | 40 | 450 | 28 |

Add -P to model number to make Platinum Unit All dimensions are in inches, weight is in pounds, 480 volt amp draw were applicable is approximately $\frac{1}{2}$ or 230 volt amp draw

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.





