19 cfm Gas Compressor/Generator

19 cfm @ 175 psi 5000 Watt Generator

Features

- Access to compressor valves without compressor head removal
- Alternator on drive engine
- ASME tested powder coated steel tank
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Critical controls protected by compressor base plate
- Disk and spring valves
- Drive engine on left side for safety
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial-duty engine
- Needle bearings, and inserts on rods
- Pilot valve continuous operation
- Swedish steel valves
- Torrington needle bearings
- 2-grove B width drive pulley

Platinum Compressor Features

- Automatic tank drain
- Belt guard aftercooler
- On-board battery mounted and wired (No truck wiring needed)
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Platinum unit




| Model | НР | Mount | Tank | Drive Engine | Length | Width | Height | Weight | | |
|---|----|-------|----------------------|--------------|--------|-------|--------|--------|--|--|
| CI13GEH30-GEN | 13 | Tank | 30 Gallon Horizontal | Honda | 44 | 22 | 42 | 550 | | |
| CI14GEK30-GEN | 14 | Tank | 30 Gallon Horizontal | Kohler | 44 | 22 | 42 | 550 | | |
| Add -P after part number to make Platinum Model | | | | | | | | | | |

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.







23 cfm Gas/Diesel Engine Compressor/Generator

Features

- Access to compressor valves without compressor head removal
- Alternator on drive engine
- ASME tested powder coated steel tank
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Critical controls protected by compressor base plate
- Disk and spring valves
- Drive engine on left side for safety
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial-duty engine
- Needle bearings, and inserts on rods
 5000 Watt Generate
- Pilot valve continuous operation
- Swedish steel valves
- Torrington needle bearings
- 2-grove B width drive pulley

Platinum Compressor Features

- Automatic tank drain
- Belt quard aftercooler
- On-board battery mounted and wired (No truck wiring needed)
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Generator Features

- 5500 Watt Generator
- 110/220 volt outlets
- 41 amps @ 120 volt
- 20 amps @ 240 volt

23 cfm @ 175 psi 5500 Watt Generator



Air cooled after cooler Platinum unit



| Model | HP | Mount | Tank | Drive engine | Length | Width | Height | | | |
|---|----|-------|----------------------|---------------|--------|-------|--------|--|--|--|
| CI18GEH30-GEN | 18 | Tank | 30 Gallon Horizontal | Honda | 44 | 22 | 42 | | | |
| CI18GEK30-GEN | 18 | Tank | 30 Gallon Horizontal | Kohler | 44 | 22 | 42 | | | |
| CI18DEK30-GEN | 18 | Tank | 30 Gallon Horizontal | Kohler Diesel | 44 | 26 | 42 | | | |
| Add -P after part number to make Platinum Model | | | | | | | | | | |

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

