### **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves

### **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

36 cfm @ 175 psi (Time Delay) 18.5 cfm @ 175 psi


(Alternating)

= Swedisti steel valves			
■ TEFC drive motor (3 phase only)			
<ul><li>Torrington needle bearings</li></ul>			
<ul><li>2-grove B width motor pulley</li></ul>			
<ul> <li>2-piece tank top plate design</li> </ul>	UNIT A	UNITB	

Model	Phase	Voltage	Tank	Length	Width	Height
DCI521E120H	1	208-230	120 Gallon	86	30	50
DCI523E120H	3	208-230-460	120 Gallon	86	30	50
Add -P to model number to make Platinum Unit						

No Start Up Kit Required Optional 5-year Pump Warranty Available

## **Industrial Gold**





# 7.5 HP Duplex

### **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves

■ TEFC drive motor (3 phase only)

Torrington needle bearings2-grove B width motor pulley

2-piece tank top plate design

### **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Platinum unit




Model	Phase	Voltage	Tank	Length	Width	Height
DCI7521E120H-CI10	1	208-230	120 Gallon Horizontal	86	30	50
DCI7523E120H-CI10 3	3	208-230-460	120 Gallon Horizontal	86	30	50
Add -P to model number to make Platinum Unit						

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

## **Industrial Gold**

**Quality Air Compressors at a Great Price.** 



40.6 cfm @ 175 psi (Time Delay)

24 cfm @ 175 psi

(Alternating)

# 7.5 HP Duplex Heavy Duty

### **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

### **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Platinum unit




Model	Phase	Voltage	Tank	Length	Width	Height
DCI7521E120H-CI10	1	208-230	120 Gallon	86	30	50
DCI7523E120H-CI10	3	208-230-460	120 Gallon	86	30	50
DCI7521E240H-CI10	1	208-230	240 Gallon	86	40	58
DCI7523E240H-CI10	3	208-230-460	240 Gallon	86	40	58
Add -P to model number to make Platinum Unit						

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

## **Industrial Gold**

**Quality Air Compressors at a Great Price.** 





60 cfm @ 175 psi (Time Delay)

28 cfm @ 175 psi

(Alternating)

#### **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

### **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Platinum unit

10 hp 1 Phase 68 cfm @ 175 psi (Time Delay) 34 cfm @ 175 psi (Alternating)

10 hp 3 Phase 70 cfm @ 175 psi (Time Delay) 35 cfm @ 175 psi (Alternating)



Model	Phase	Voltage	Tank	Length	Width	Height
DCI1021E120H	1	208-230	120 Gallon	86	30	50
DCI1023E120H	3	208-230-460	120 Gallon	86	30	50
DCI1021E240H	1	208-230	240 Gallon	86	40	58
DCI1023E240H	3	208-230-460	240 Gallon	86	40	58
Add -P to model number to make Platinum Unit						

No Start Up Kit Required • Optional 5-year Pump Warranty Available

## **Industrial Gold**



### **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

### **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

106 cfm @ 175 psi (Time Delay) 53 cfm @ 175 psi (Alternating)




Air cooled after cooler Platinum unit



Model	Voltage	Tank	Length	Width	Height
DCI1523E248H	208-230/460-480	240 Gallon	85	50	70
Add -P to model number	to make Platinum Unit				

No Start Up Kit Required • Optional 5-year Pump Warranty Available

## **Industrial Gold**





### **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

### **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

150 cfm @ 175 psi (Time Delay) 75 cfm @ 175 psi (Alternating)




Air cooled after cooler Platinum unit



Model	Voltage	Tank	Length	Width	Height
DCI2023E240H	208-230/460-480	240 Gallon	85	52	72
Add -P to model number	to make Platinum Unit				

No Start Up Kit Required • Optional 5-year Pump Warranty Available

## **Industrial Gold**





### **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

### **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

184 cfm @ 175 psi (Time Delay) 92 cfm @ 175 psi (Alternating)



Air cooled after cooler Platinum unit



Model	Voltage	Tank	Length	Width	Height
DCI2523E240H	208-230/460-480	240 Gallon	85	52	72
Add -P to model number	to make Platinum Unit				

No Start Up Kit Required • Optional 5-year Pump Warranty Available

## **Industrial Gold**



