

5 HP Reciprocating

17.5 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-groove B width motor pulley
- 2-piece tank top plate design

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI521E60V	1	208-230	60 Gallon Vertical	32	24	74	24	N/A
CI523E60V	3	208-230	60 Gallon Vertical	30	25	74	16	8
CI521E80V	1	208-230	80 Gallon Vertical	32	26	78	24	N/A
CI521E80H	1	208-230-460	80 Gallon Horizontal	63	24	45	16	N/A
CI523E80V	3	208-230	80 Gallon Vertical	32	26	78	24	8
CI523E80H	3	208-230-460	80 Gallon Horizontal	63	24	45	16	8

Add -P after model number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019



7.5 HP Heavy Duty Reciprocating


28 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Elite unit



Model	Phase	Voltage	Tank	Length	Width	Height
CI7521E80V-CI10	1	208-230	80 Gallon Vertical	42	34	84
CI7523E80V-CI10	3	208-230-460	80 Gallon Vertical	42	34	48
CI7521E80H-CI10	1	208-230	80 Gallon Horizontal	63	24	45

Add -P after part number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019



7.5 HP Reciprocating

24 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI7521E80V	1	208-230	80 Gallon Vertical	32	26	78	32	N/A
CI7523E80V	3	208-230-460	80 Gallon Vertical	32	26	78	18	9
CI7521E80H	1	208-230	80 Gallon Horizontal	63	24	45	32	N/A
CI7523E80H	3	208-230-460	80 Gallon Horizontal	63	24	45	18	9
CI7521E120V-CI5	1	208-230	120 Gallon Vertical	42	34	84	32	N/A
CI7523E120V-CI5	3	208-230-460	120 Gallon Vertical	42	34	84	18	9
CI7521E120H-CI5	1	208-230	120 Gallon Horizontal	70	26	45	32	N/A
CI7523E120H-CI5	3	208-230-460	120 Gallon Horizontal	70	26	45	18	9

Add -P after part number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019



10 HP Reciprocating

34.5 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design



Air cooled after cooler Platinum unit



Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI1021E80V	1	208-230	80 Gallon Vertical	36	24	74	42	N/A
CI1023E80V	3	208-230-460	80 Gallon Vertical	36	24	74	28	14
CI1021E80H	1	208-230	80 Gallon Horizontal	64	24	48	42	N/A
CI1023E80H	3	208-230-460	80 Gallon Horizontal	64	24	48	28	14
CI1021E120V	1	208-230	120 Gallon Vertical	42	34	84	42	N/A
CI1023E120V	3	208-230-460	120 Gallon Vertical	42	34	84	28	14
CI1021E120H	1	208-230	120 Gallon Horizontal	70	26	45	42	N/A
CI1023E120H	3	208-230-460	120 Gallon Horizontal	70	26	45	28	14

Add -P after part number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019



15 HP 45 cfm Reciprocating

45 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-groove B width motor pulley
- 2-piece tank top plate design



Air cooled after cooler Platinum unit

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Lenght	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI153E120V	3	208-230-460	120 Gallon Vertical	42	34	84	28	14
CI153E120H	3	208-230-460	120 Gallon Horizontal	70	26	45	28	14

Add -P after part number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019



15 HP 51 cfm Reciprocating

51 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design



Air cooled after cooler Platinum unit

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Lenght	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI1523E120H-CA3	3	208-230-460	120 Gallon Horizontal	70	26	54	42	21
CI1523E240H-CA3	3	208-230-460	240 Gallon Horizontal	85	30	60	42	21

Add -P after part number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019



20 HP Reciprocating

78 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Platinum unit



Model Number	Phase	Voltage	Tank	Lenght	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI2023E120H	3	208-230-460	120 Gallon Horizontal	70	38	60	54	27
CI2023E240H	3	208-230-460	240 Gallon Horizontal	85	46	72	54	27

Add -P after part number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019



25 HP Reciprocating

90 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Platinum unit



Model Number	Phase	Voltage	Tank	Lenght	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI2523E120H	3	208-230-460	120 Gallon Horizontal	70	38	60	63	32
CI2523E240H	3	208-230-460	240 Gallon Horizontal	85	46	72	63	32

Add -P after part number to make Platinum Model

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

