Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Compressor

Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines

70 dBA 16 cfm @ 150 psi 19 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R51ENC			80 Gallon Horizontal Basic		32	28	42	24	N/A
R53ENC	3	208-230-460	80 Gallon Horizontal	Basic	32	28	42	16	8
Add –CDR after model number for CDR rackage.									

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold



Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Compressor

Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines


70 dBA 26 cfm @ 150 psi 29 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt		
R71ENC	1	208-230	80 Gallon Horizontal	32	28	42	32	N/A		
R73ENC	R73ENC 3 208-230-460		80 Gallon Horizontal	32	28	42	18	9		
Add –CDR after model number for CDR package.										

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold





Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads



71 dBA



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt	
R101ENC	1	208-230	80 Gallon Horizontal	32	28	42	44	N/A	
R103ENC	3	208-230-460	80 Gallon Horizontal	32	28	42	28	14	
Add –CDR after model number for CDR package.									

No Start Up Kit Required Optional 5-year Pump Warranty Available

Industrial Gold





15 HP | 57 cfm Enclosed Rotary Screw

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Compressor Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads

■ Free freight in the 48 states &





Model Number	Phase	Voltage	Tank Package		Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt	
R153ENC	3	208-230-460	N/A	Basic	32	28	42	42	21	
R153ENC-CDR	3	208-230-460	80 Gallon Horizontal	CDR	68	28	42	42	21	

No Start Up Kit Required Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price. industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364



Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads

73 dBA 75 cfm @ 150 psi

88 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R203ENC	3	208-230-460	80 Gallon Horizontal	Basic	41	36	46	24	N/A
R203ENC-CDR	3	208-230-460	80 Gallon Horizontal	CDR	64	37	68	24	N/A

No Start Up Kit Required Optional 5-year Pump Warranty Available

Industrial Gold



25 HP | 108 cfm Enclosed Rotary Screw

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads

77 dBA 102 cfm @ 150 psi

108 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R253ENC	3	208-230-460	N/A	Basic	42	43	59	63	32
R253ENC-CDR	3	208-230-460	120 Gallon Vertical	CDR	42	43	59	63	32

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold



Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Compressor

Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads

77 dBA 125 cfm @ 150 psi 130 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R303ENC	3	208-230-460	N/A	Basic	42	43	59	72	36
R303ENC-CDR	3	208-230-460	120 Gallon Vertical	CDR	42	43	59	72	36

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price. industrialgold.com **•** 1-800-531-9656 **•** Fax 972-352-6364



Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads

77 dBA 155 cfm @ 150 psi 160 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R403ENC	3	208-230-460	N/A	Basic	57	44	60	92	46
R403ENC-CDR	3	208-230-460	120 Gallon Vertical	CDR	57	44	60	92	46

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold



Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads
- Free freight in the 48 states

78 dBA 185 cfm @ 150 psi 215 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R503ENC	3	208-230-460	N/A	Basic	57	44	60	125	63
R503ENC-CDR	3	208-230-460	120 Gallon Vertical	CDR	57	44	60	125	63

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold



Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads
- Free freight in the 48 states

79 dBA 225 cfm @ 150 psi 245 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R603ENC	3	208-230-460	N/A	Basic	57	44	60	144	72
R603ENC-CDR	3	208-230-460	120 Gallon Vertical	CDR	57	44	60	144	72

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold



75 HP | 335 cfm Enclosed Rotary Screw

Features

 Airend manufactured with German rotary screw components

■ Air/oil cooler

Automatic belt tensioning

Easy to read and access gauges

Easy to access oil cooler for cleaning

■ Extended oil drain with ball valve for easy service

■ Factory filled with premium synthetic fluid

■ Heavy duty air filter

Omega profile rotors

Operating pressures from 100-190 psi available

 Simplified operating controls, no complicated micro-processor

■ Single control solenoid operation

■ Spin on oil filter

Solid steel sound enclosure

■ Spin on separator

■ TEFC drive motor (3 phase only)

UL control components

Vertical draft ventilation

80 dBA 295 cfm @ 150 psi 335 cfm @ 125 psi



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS753ENC	3	208-230-460	N/A	Basic	84	60	60	172	86

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold





Features

 Airend manufactured with German rotary screw components

■ Air/oil cooler

Automatic belt tensioning

Easy to read and access gauges

Easy to access oil cooler for cleaning

■ Extended oil drain with ball valve for easy service

Factory filled with premium synthetic fluid

■ Heavy duty air filter

Omega profile rotors

Operating pressures from 100-190 psi available

 Simplified operating controls, no complicated micro-processor

■ Single control solenoid operation

■ Spin on oil filter

■ Solid steel sound enclosure

■ Spin on separator

■ TEFC drive motor (3 phase only)

UL control components

Vertical draft ventilation





Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R1003ENC	3	208-230-460	N/A	84	60	60	238	119

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold



