13-14 HP | 28-30 cfm Engine Driven Rotary Screw

Features

- Airend manufactured with German rotary screw components
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Industrial-duty drive engine
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- UL control components

Platinum Compressor Features

- Air/oil cooler
- Battery mounted and wired
- SIMPLEX controls
- Tank discharge ball valve
- Vibration isolation pads
- Freight pre-paid in the 48 states & southern Canada

13 HP 28 cfm @ 150 psi 14 HP 30 cfm @ 150 psi



Model	HP	Mount	Tank	Drive engine	Length	Width	Height
R10DEK30	10	Tank mount	30 Gallon Horizontal	Kohler Diesel	48	24	48
R13GEH30	13	Tank mount	30 Gallon Horizontal	Honda	48	24	48
R14GEK30	14	Tank mount	30 Gallon Horizontal	Kohler	48	24	48
Unit does not come standard with a fuel tank Add -P to model number to make Platinum Unit							

No Start Up Kit Required • Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

