

About us





Ing. **Enea Mattei SpA** is an Italian company that has been producing air compressors since 1919. Over the years, the company has continually evolved and is today one of the world's foremost companies in the compressed air sector and the leader in the production of rotary vane compressors.

Behind the success of Mattei are the choice the company has made in terms of design, production and marketing, driven by the results of its continual and in-depth research and development programmes.

During these years of continual change, Mattei has been able to adapt to the requirements of the market and through the results of its research has created products that are always innovative and technologically advanced.



Certified quality

Quality as an integral part of all company functions and constant improvement of all production processes so as to always guarantee the maximum level of reliability and satisfaction. This, in brief, is the value and the meaning of **Mattei's** operational philosophy. A way of approaching the market and customers that makes **Mattei** an absolute point of reference in the compressed air sector.

Since 1994, **Mattei** has been operating with a Quality System certified by the DNV Institute under UNI EN ISO 9001 regulations.







PERFECTLY ENGINEERED - PERFECTLY MATTEI Ideal for industrial use and 24 hour a day operation

Mattei's new range of small industrial compressors is designed to satisfy compressed air demand in those applications where the operating characteristics and reliability needs are higher than those available from other compressors on the market.

Direct coupling

Mattei has always produced compressors in wich the eletric motor, which turns at a speed of only 1,800 rpm, is directly coupled to the compression unit by means of a flexible joint. This direct, in-line coupling results in considerable energy saving as there are no losses due to the presence of pulley wheels and drive belts.



Durable and quiet

The Classic compressors are robust, resistant to corrosion and are particularly compact and ideal for installation in small spaces. The vane technology ensures safe and quiet operation even without a noise reducing outer canopy.





Operating principle



Maximum efficiency of the air compression process, excellent reliability and low running costs; are just some of the key benefits that rotary vane technology can offer.


The vane compressor is a volumetric rotary compressor that consists of a stator cylinder in wich a rotor is mounted off-centre but parallel to its sides.

The rotor has slots in wich the vanes are free to slide: centrifugal force keeps them in contact with the sides of the stator during rotation. The rotary vane compressor, thanks to its **simple construction**, offers

remarkable advantages, first among them being **greater volume yield** because the vanes are in constant contact with the inner wall of the stator and form a perfectly airtight seal with no leaks along the wall thanks to a continuous film of oil.

In this type of compressor no axial thrust is generated so the side surfeces of the rotor are not subject to wear and thus no rotating bearings or thrust bearings are needed. The vanes, too, because of the special way they are made have practically **unlimited life.**

Behind the success of Mattei compressors there is thus **extreme reliability, long life, quiet operation and simplicity of maintenance.** Design is important too: compactness and clean lines, together with harmonious shapes, give Mattei compressors an image of robustness and ease of use.



Features

- DIRECT COUPLING THROUGH FLEXIBLE JOINT
- ▶ OIL RADIATOR AND CENTRIFUGAL COOLING FAN
- ► AIR DELIVERY AUTOMATIC CONTROL WITH CONSTANT PRESSURE
- ► THERMO DYNAMICALLY BALANCED INLET AIR FLOW TO ENSURE MAXIMUM EFFICIENCY OF THE COMPRESSOR
- ► THERMOSTATIC VALVE ENSURES OPTIMUM OPERATING TEMPERATURE AND ENERGY EFFICIENCY



- > STARTER WITH MAGNETOTHERMAL PROTECTION
- ▶ SAFETY THERMOSTAT FOR HIGH OIL TEMPERATURE
- ON BOARD PRESSURE GAUGE
- ▶ VISUAL OIL LEVEL INDICATOR
- ▶ FACTORY-FILLED WITH ROTOROIL F2 SYNTHETIC LUBRICANT
- ► HIGH EFFICIENCY INTAKE FILTER
- ▶ AFTERCOOLER AND CONDENSATE DRAIN





60 Hz

	4			O									i	
Model	Tension	Power		10 bar 145 psig		Sound pressure level	Length		Width		Height		Weight	
	V/f	kW	hp	m³/min	cfm	dB(A)	mm	inch	mm	inch	mm	inch	kg	lbs
ERC 1-S	230/1	1.5	2	0,14	5.1	66	740	29.2	390	15.37	432	17	50	110
ERC 2-S	230/1	2.2	3	0,19	6.7	66	740	29.2	390	15.37	432	17	55	121
ERC 1-T	460/3	1.5	2	0,14	5	66	740	29.2	390	15.37	432	17	50	110
ERC 2-T	460/3	2.2	3	0,19	6.7	66	740	29.2	390	15.37	432	17	55	121

F.A.D. in accordance with ISO 1217, annex "C" | Sound pressure level according to ISO 2151, tolerance \pm 3dB(A) | Working pressure: 7,5 bar for version 8 bar - 9,5 bar for version 10 bar - 12,5 bar for version 13 bar

PRESSURE SWITCH KIT	
230v/1ph/60Hz kit	20010895
460v/3ph/60Hz kit	20010896

