Specifications

Port Sizes 3/8", 1/2", 3/4", 1" **Thread Styles** NPT, BSPT, BSPP

Flow Capacity 60/120/175 SCFM @ 100 PSI

Filter Capacity Differential Pressure Max. Temp./Pressure

Description

3.0 micron & larger < 5.0 PSID at rated flow

(Aluminum Bowl) 175°F/200 PSIG Approx. Weight (lb.) 3.5/6.0/6.0 **ISO Class** 3 Particulate




Part Number


Water Dirt Oil Oil Vapor Odor

For higher pressure applications, consult factory. Units equipped with differential pressure indicator have max. temperature and pressure of 125°F and 150 PSIG, regardless of bowl material.

Replacement Parts & Accessories



Α	Replacement Element	1P-060/1P-120/1P-175
В	Differential Pressure Indicator	N32-W1-DPi-FG
В	Blanking Cap (Cover for units without indicator)	N32-95-020-FG
C	Bowl Assembly: Metal Bowl, Manual Petcock Drain, O-ring (60)	N34-95-205-FG
C	Bowl Assembly: Metal Bowl, Automatic Float Drain, O-ring (60)	N34-95-195-FG
C	Bowl Assembly: Metal Bowl, Manual Petcock Drain, O-ring (120/175)	N34-15-180-FG
C	Bowl Assembly: Metal Bowl, Automatic Float Drain, O-ring (120/175)	N34-15-185-FG
D	Manual Petcock Drain	PC-03
Ε	Automatic Float Drain	N32-95-973-FG
F	Bowl O-ring (60)	N32-95-257
F	Bowl O-ring (120/175)	N32-95-256



Order Guide

Drain Type	Port Size	Model Number
	3/8"	1P-060-F03-P
Manual	1/2"	1P-060-F04-P
Manual	3/4"	1P-120-F06-P
	1"	1P-175-F08-P

	3/8"	1P-060-F03-F
Automatic	1/2"	1P-060-F04F
Automatic	3/4"	1P-120-F06F
	1"	1P-175-F08F

Di	mensions (i	sions (in.)		
Height*	Width	Depth		
10.0	3.9	3.9		
10.0	3.9	3.9		
17.0	4.6	4.8		
17.0	4.6	4.8		

10.0	3.9	3.9
10.0	3.9	3.9
17.0	4.6	4.8
17.0	4.6	4.8

Food Grade certified non-toxic powder coated filters meet requirements of 21 CFR 100. Coating ingredients meet at least one section of FDA Title 21, with the exception of food items containing 8% alcohol.

^{*}To add an indicator, add "i" to end of model number (Indicator adds about 1" to height)