

Cool Pak *PRO*

The Most Efficient Aftercooler Package on the Market.

The Cool Pak PRO is an aftercooler system with a filter/separator which is similar to our Cool Pak but with one distinct difference. We have placed it on a cart for mobility purposes. After further testing of our original Cool Pak we realized having the filter/separator at the high point in the aftercooler system can sometimes cause issues. The liquid created through cooling the compressed air always falls down to the bottom of the aftercooler since water is heavier than air. Water accumulating and flooding the bottom of the cooler drastically decreases performance because there is less capacity for the compressed air to be cooled. The Cool Pak PRO solves this problem by being the only aftercooler system designed to be laid down on its back! In this orientation, the swivel filter/separator is moved to the low point in the system which allows it to actually function as intended. This makes the Cool Pak Pro the most efficient aftercooler system on the market today!

Its affordable, completely portable, and allows for two operating positions. You can hook it up vertically or lay the Cool Pak Pro down which allows for optimal performance. The cart provides ease of use at the jobsite with a low profile handle and wheels; moving from jobsite to jobsite is simple. The idea of this Cool Pak Pro is to allow jobs to have clean, cool compressed air with the most efficient aftercooler package available on the market.

The Cool Pak PRO is ideal for:

- Portable Blasting
- Construction Sites
- Protecting Air Tools
- Small Blast Pots
- Portable 250 Compressors

F E A T U R E S

Air-cooled aftercooler with air motor

250 SCFM max flow rating

Portable cart

Dual operating positions

Transporting Position



Optimal Operating Position



BENEFITS OF THE Cool Pak *PRO*

Versatile // No Electricity Required // Superior Performance

vanairsystems.com

STANDARD EQUIPMENT

- Air Motor Air-cooled aftercooler
- (1) F200 Series Filter/ Separator
- 250 SCFM Max Flow Rating
- Portable Cart
- Forklift accessibility

DIMENSIONS & SPECIFICATIONS

Model No.	HEIGHT		WIDTH		DEPTH		Inlet Conn. (in)	Outlet Conn. (in)	Flow Rating SCFM	Air Motor SCFM	Weight	
	in	cm	in	cm	in	cm					lbs	kg
CPP-185	36	91	23	58	27	68	1 1/4 NPT	1 1/4 NPT	250	22	160	73

2950 Mechanic Street, Lake City, PA 16423, USA | Toll Free Phone 800-840-9906 | Corporate Fax 814-774-0778 | Order Entry Fax 814-774-3482

Distributed By:





Cool Pak Pro - PDF Downloads

Instruction Manuals

Coming
Soon

Sales Drawings

Coming
Soon