







## **NOTES & SPECIFICATIONS:**

MODEL #: WL-825-NW25EN

- 1. FLANGES TO BE PROTECTED DURING PRODUCTION & SHIPMENT.
- 2. UNIT TO BE HELIUM LEAK TESTED TO 1 x 10-5 mbar L/s.

	ELEMENT SPECS				
	PART NUMBER 825		325		
	MATERIAL	Polyester			
	FLOW RATE	25 CFM	42 m³/hr		
	SURFACE AREA	0.4 ft <sup>2</sup>	0.0 m <sup>2</sup>		
	I.D.	1.50"	38mm		
	O.D.	2.50"	64mm		
	HEIGHT	2.69"	68mm		
MATERIAL: CARBON STEEL		FINISH: ELE	CTROLESS NICKEL		

**SOLBERG**® Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE
TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

## **TOLERANCES**

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.** 

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBED.	BER: WL-825-NW25EN	SHEET:
WODEL NOWBER.	VVL-023-INVVZ3EIN	1 OF 1

**DESCRIPTION:** WL-825-NW25EN, ELECTROLESS NICKEL

PROJECT:	DRAWN BY: EZR	APPROVED BY: CRW	REV
SD19010	<b>DATE</b> : 2/1/2013 <b>DATE</b> : 2/1/2013	<b>DATE</b> : 2/1/2013	Α