


## FLANGE FACE SURFACES TO BE FREE OF SCRATCHES, DIVOTS, OR ANY DEFORMATION THAT AFFECTS SEAL. FLANGE FACES TO BE PROTECTED DURING SHIPMENT.



REV	DESCRIPTION	ECN #	CHG BY	DATE	APP'D
Α	UPDATED PART NUMBER, WAS CSL	15527	EZR	02/14/19	TAS
В	UPDATED ELEMENT SPECS	17839	TAS	12/04/19	NAD



NOTES & SPECIFICATIONS:

1. FLANGES TO BE PROTECTED DURING PRODUCTION & SHIPMENT.

2. UNIT TO BE HELIUM LEAK TESTED TO 1 x 10-5 mbar L/s.

			ELEMENT SPECS								
			PART NUMBER	851 POLYESTER							
			MATERIAL								
			FLOW RATE			493 m <sup>3</sup>					
			SURFACE AREA			0.4 r					
			I.D.	3	.50" 89m		าท				
			0.D.	5.88" 14		149m	)mm Lmm				
			HEIGHT	8	8.69" 221r						
	MODEL #: WL-851-K63B	MATERIAL: CARBON STEEL FINISH:				CK POWDER					
	MODEL NUMBER: WL-851-K63B						<b>SHEET:</b> 1 OF 2				
GE	DESCRIPTION: WL-851-K63B, BLACK										
APPLY	PROJECT:		DRAWN BY: CRW DATE: 3/18/2013		<b>APPROVED BY:</b> M.C. <b>DATE:</b> 3/18/2013			REV:			
R								В			