



Refrigerated
Compressed
Air Dryers
HRHT Series
High Inlet Temperature
15 to 100 SCFM
25.5 to 169.9 NM³/H

Designed for reliable high-temp drying up to 200°F while delivering sustainable performance through low-GWP R513A refrigerant across the 15-100 SCFM range.

**Engineered for performance, reliability,
and environmental responsibility**

The Hankison HRHT Series delivers consistent moisture removal in demanding, high-temperature applications. Designed to handle inlet air temperatures up to 200°F, these dryers offer durable construction, easy installation, proven efficiency, and a climate-friendly refrigerant that supports long-term sustainability goals.



Easy Operation & Maintenance

- **Integrated moisture separator** reliably removes water and oil without manual draining.
- **Operated zero-loss drain.**
- **Automatic refrigeration controls** maintain stable chilled air temperatures and prevent freeze ups-ups.
- **115V/60Hz plug and play design** simplifies setup across all models.
- **Smart controller** (60-100 SCFM models) includes LED indicators, alarm history, and energy saving fan control-saving fan control.

Performance Advantages

- **Built for extreme conditions:** Designed and tested to perform reliably in high-temp, high-humidity environments where standard dryers fail.
- **Reduced total cost of ownership:** Integrated pre-cooling, moisture separation, and minimal pressure drop reduce installation cost and energy consumption.
- **Reliable moisture protection:** Consistent dew point performance supports paintquality air, clean pneumatic controls, and downstream equipment protection.
- **Sustainable refrigerant choice:** R513A delivers strong cooling performance with a substantially lower global warming potential compared to legacy refrigerants.

Better By Design

- High-Temp Performance rated for 200°F inlet air to match harsh operating conditions.
- Efficient Heat Exchangers.
15-35 SCFM: Brazed plate.
60-100 SCFM: Aluminum plate-fin.
- Aftercooler + condenser combination on 60-100 SCFM models for improved cooling stages and lower dew points.
- Environmentally responsible R513A refrigerant with low GWP.
- UL and CSA certified to leading North American standards for safety and quality.

Product Specifications

Model	Inlet Flow		Pressure Drop PSID	Voltages	In/Out Air Connect Size	Power Consumption kW	Refrigerant	Dimensions			Ship Weight	
	SCFM*	NM ³ /H						W in.	D in.	H in.	lbs.	kg
HRHT15A	15	25.5	0.8	115/1/60	3/4" MNPT	0.48	R513A	14.6	16.9	29.7	110	46.7
HRHT25A	25	42.5	1.8	115/1/60	3/4" MNPT	0.51	R513A	14.6	16.9	29.7	110	46.7
HRHT35A	35	59.5	2.5	115/1/60	3/4" MNPT	0.64	R513A	14.6	16.9	29.7	117	49.9
HRHT60A	60	101.9	4.8	115/1/60	3/4" FNPT	0.61	R513A	16.6	22.4	30.0	123	63.1
HRHT80A	80	135.9	3.8	115/1/60	3/4" FNPT	0.77	R513A	16.6	22.4	30.0	128	64.0
HRHT100A	100	169.9	6.4	115/1/60	1" FNPT	1.16	R513A	16.6	22.4	30.0	132	68.0

Choose the HRHT Series for reliable, sustainable, and high-temperature moisture removal.

Visit hankisonair.com or contact your authorized Hankison distributor for full technical details and sizing assistance.

Refrigerated Compressed Air Dryers

HRHT Series 15 to 100 SCFM (25.5 to 169.9 NM³/H)

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region.

Hankison Headquarters

4647 SW 40th Avenue, Ocala,
Florida 34474-5788 U.S.A.

Tel.: (724) 745-1555

Fax: (724) 745-6040

Hankison Rental

100 Commerce Dr.,
Washington, PA 15301

Tel.: (724) 225-1470

Fax: (724) 222-1317

10399 New Decade Drive,
Pasadena, TX 77507

Tel.: (800) 379-3711

hankisonair.com

