

NUTRUNNER STANDARD VERSION



BATTERY POWERED

3/4" - 1" - 1 1/2"

PROFESSIONAL DUTY RANGE



NUTRUNNER

MAIN FEATURES

TYPE OF POWER SUPPLY



Cordless

PACKAGING



Provided in hard case

BEST FOR



Industrial assembly



Mechanical workshops

| PRODUCT NAME | DP05-34B | DP10-34B | DP20-10B | DP30-10B | DP36-10B | DP48-15B | DP80-15B |
|--------------|----------------------------|------------------------------|-------------------------------|-------------------------------|-------------------------------|--------------------------------|-------------------------------|
| PRODUCT CODE | A.08.0017 | A.08.0018 | A.08.0019 | A.08.0020 | A.08.0021 | A.08.0028 | A.08.0029 |
| SQUARE DRIVE | 3/4" | 3/4" | 1" | 1" | 1" | 1 1/2" | 1 1/2" |
| BOLT RANGE | M24-95 | M27-95 | M27-95 | M36-95 | M36-95 | M52-95 | M72-300 |
| TORQUE RANGE | 130-550 Nm 95-370 ft-lb | 180-1000 Nm 130-740 ft-lb | 220-2000 Nm 160-1480 ft-lb | 330-3000 Nm 240-2220 ft-lb | 380-3600 Nm 280-2660 ft-lb | 500-4800 Nm 368- 3540 ft-lb | 900-8000 Nm 664-5900 ft-lb |
| PRESSURE | 87 psi - 6 bar | 87 psi - 6 bar | 87 psi - 6 bar | 87 psi - 6 bar | 87 psi - 6 bar | 87 psi - 6 bar | 87 psi - 6 bar |
| SPEED | 71,6 rpm | 48,0 rpm | 24,6 rpm | 20,9 rpm | 15,3 rpm | 12,9 rpm | 5,7 rpm |
| WEIGHT | 11.7 lbs 5,3 kg | 11.7 lbs 5,3 kg | 15.0 lbs 6,8 kg | 15.0 lbs 6,8 kg | 15.0 lbs 6,8 kg | 27.6 lbs 12,5 kg | 27.6 lbs 12,5 kg |
| LENGTH | 365 mm 14.37 in | 365 mm 14.37 in | 405 mm 15.95 in | 405 mm 15.95 in | 405 mm 15.95 in | 437 mm 17.20 in | 522 mm 20.55 in |



DOWNLOAD THE MANUAL

