

QV Rotary Vane Pumps 1.2 - 10 HP

The QV is an oil-sealed rotary vane vacuum pump, perhaps the most "tried and true" vacuum technology on the market. The simplicity of the maintenance and operation, make the QV a great total cost of ownership solution. These pumps are used in many applications, either by themselves or incorporated into standard systems. The pumps have been redesigned to allow for continuous duty operation from atmospheric pressure to ultimate vacuum!



- Integral non-return valve on inlet connection
- 2 Direct Driven, no belts
- 3 Exhaust Filter Elements remove 99% of entrained oil
- 4 Air-Cooled, no cooling water requirements
- 5 Easy to change oil filter protects pumping chamber

QV Series 1.2-10 HP

The QV Is Best For:

- ✓ Low Flowrate, point-of-use applications
- Air (or littler water vapor) process gases
- Facilities looking fors simple DIY maintenance
- **Solution** Food processing

- Food Packaging/Preservation
- ✓ Degassing/Drying
- ✓ Vacuum Load Locks/Fixtures
- Pick and Place

QV 01-10 TECHNICAL DATA

| Model No. | Ultimate Pressure | | Volumetric Flowrate | | Installed Motor | | Max Noise Level |
|--------------|-------------------|-------|---------------------|--------------------|-----------------|------|--------------------|
| | "HgV | mbara | ACFM | m ³ /hr | HP | kW | dB(A) |
| QV-01 | 29.9 | 0.5 | 17.1 | 29 | 1.2 | 0.90 | 59 |
| QV-02 | 29.9 | 0.5 | 31.2 | 53 | 1.7 | 1.3 | 60 |
| QV-03 | 29.9 | 0.5 | 41.8 | 71 | 2.4 | 1.8 | 64 |
| QV-05 | 29.9 | 0.5 | 68.9 | 117 | 4.8 | 3.6 | 64 |
| QV-07 | 29.9 | 0.1 | 141 | 240 | 7.4 | 5.5 | 73 |
| QV-10 | 29.9 | 0.1 | 100 | 340 | 8.8 | 6.6 | 76 |

QV 01-10 DESIGN/DIMENTIONAL DATA

| Model No. | Standard Dimensions | | | Weight | | Inlet Size | Outlet | Oil Capacity |
|--------------|---------------------|------------------|-------------------|--------|-----|------------|------------|--------------|
| | Length (in/mm) | Width (in/mm) | Height (in/mm) | lb | Kg | (NPT) | Size (NPT) | (US Quart) |
| QV-01 | 15.2 / 387 | 9 / 231 | 9.7/246 | 75 | 34 | 1/2" | 1/2" | 2.1 |
| QV-02 | 21 / 533 | 11.2 / 285 | 10 / 255 | 88 | 40 | 1 1/4" | 1 1/4" | 1.1 |
| QV-03 | 23 / 580 | 12.6 / 320 | 10.5 / 266 | 106 | 48 | 1 1/4" | 1 1/4" | 2.1 |
| QV-05 | 30 / 765 | 15.7 / 398 | 10.7 / 271 | 203 | 92 | 1 1/4" | 1 1/4" | 2.1 |
| QV-07 | 38 / 965 | 23 / 586 | 16 / 407 | 397 | 180 | 2" | 2" | 7.9 |
| QV-10 | 43 / 1090 | 21.8 / 555 | 17.7 / 450 | 476 | 216 | 2" | 2" | 9-12.2 |

Standard Features

Gas Ballast

✓ Initial fill of synthetic oil

Available Options and Accessories

✓ Oil Level and High Temperature Switches

✓ Inlet filter, inlet check valve, vacuum gauge, motor starter

Available as simplex, duplex and triplex systems



WARRANTY

1 Year Standard Warranty



At Quincy Compressor, we have been engineering and manufacturing the longest-lasting, highest-quality vacuum pumps and compressed air equipment for over a century. Our QV series vacuum pumps come with a one-year standard warranty, giving you extra assurance that your pump will perform in peak condition and deliver long-lasting results.

