

FINISH SPECIFICATION	SHIPPING AND PACKAGING	WELD JOINT DETAILS
ALL TANKS REQUIRE: INTERIOR AND EXTERIOR TO BE FREE OF WELD SPATTER, DRY INTERIOR AFTER HYDROTEST, VACUUM INTERIOR FREE OF LOOSE PARTICLES  PRE-ASSEMBLY SURFACE PREP:	GENERAL NOTES  PLUG ALL UNPLUGGED OPENINGS WITH PLASTIC PLUGS AFTER PAINTING BUILD SKID SO THAT TANK DOES NOT EXTEND BEYOND EDGES OF SKID USE FOAM UNDER BANDS  REFER TO SHOP ORDER - SHIPPING WORK GUIDELINES, FOR ADDITIONAL INSTRUCTIONS (IF APPLICABLE)	
POST-ASSEMBLY SURFACE PREP:	PACKAGING MATERIALS  REFER TO PALLET DRAWING	
	PALLET SIZE X COLOR CODE:  STACK PER PALLET DRAWING USING CARDBOARD, BANDS, FOAM, AND SHRINK WRAP AS APPLICABLE	
EXTERIOR FINISH:	ADDITIONAL SHIPPING INSTRUCTIONS	
POWDER PAINT EXT STD GRAY PRIMER (PL216QF)  INTERIOR FINISH:		
	DOCUMENTATION	
** DO NOT PAINT SEALING SURFACES OF FLANGES ** ** DO NOT PAINT STAINLESS STEEL NAMEPLATES **  ADDITIONAL NOTES:		
		DESIGN & CALCULATIONS COMPLY WITH ASME CODE SECTION VIII, DIV1. LATEST EDITION
OUTSIDE SERVICE VERIFICATION  WHEN PRODUCT IS SHIPPED DIRECT TO CUSTOMER FROM VENDOR, OUTSIDE VENDOR SHALL SIGN OFF INDICATING ACCEPTANCE OF ALL CRITERIA ON FINISH SPECIFICATIONS. FINISH SPECIFICATIONS SHALL BE SIGNED BY VENDOR & RETURNED TO STEEL FAB AFTER JOB IS COMPLETE.		SVPG STOCK    ENG. APP'L / DATE   JE - 1/18/2010
SIGNED DATE		DRAWN BY: KRG  DATE: 1/15/2010    DATE: 1/15/2010   DATE: 1/15/201